



## ZINC OXIDE TS-ACTIVE

### PRODUCT SPECIFICATIONS

<b>DESCRIPTION</b>	Off White Powder
<b>FORMULA</b>	Zinc Oxide
<b>CHEMICAL &amp; PHYSICAL PROPERTIES</b>	Zinc Oxide Content 94% min
	Surface Area (BET) min 40 m <sup>2</sup> /gm
	Copper as Cu 15 ppm max.
	Lead as Pb 30 ppm max.
	Cadmium as Cd 10 ppm max.
	Manganese as Mn 5 ppm max.
	Packing Density 900 g/l (±100)
	Sieve Residue (45 micron or 350 BSS) 0.05% max.
<b>PACKAGING</b>	25 Kg HDPE / paper bags (other packing available on request)
<b>STORAGE</b>	Keep it away from moisture. Store in a dry and well-ventilated place.
<b>MAJOR APPLICATIONS</b>	<ul style="list-style-type: none"><li>• Transparent activator in rubber (as partial replacement of Zinc Oxide mainly in footwear sole), feed additives, etc.</li><li>• Drilling Fluids: It is used as a sulfide scavenger for water-base drilling fluids</li></ul>



**Transpek-Silox**

Manufactured by: *Transpek - Silox Industry Limited*

Kaloli Road, Alibada, Vasdevra 390 012, India Tel: 91 265 2680401 - 05 Fax: 91 265 2680407 / 2680062 e-mail: info@tsilox.com website: www.transpek-silox.com



**TUV NORD**



**TUV NORD**